

Hot Tank



The Model 5000 Hot Tank is manufactured to Waterstone's Specifications by Anaheim Manufacturing

Model 5000 Waterstone Hot Tank

The perfect compliment to your Waterstone faucet - precision engineered and designed to give years of trouble free "instant" hot water.



Any WATERSTONE Hot or Hot and Cold Faucet 1/4" O.D. Red Line Hot Tank Inle 1/4" O.D. Blue Line Filtered Cold Water Inlet 5/16" Clear High Temperature 1/4" to 1/4" Teflon Tube. Hot Tank Outlet to Quick Connect Adapter 3/8" to 5/16" PRV Quick Connect Adapte (Pressure Regulator Valve) Requires 115V AC 750 Watts

This tank works specifically with the Waterstone Hot Only and Hot & Cold Faucets with integrated venting.

The Waterstone Model 5000 Hot Tank incorporates an ambient vent system and can not be pressurized.





Waterstone Matching Faucets & Accessories







1300 Bar Faucet



1100 Series Filtered Water Faucet

Features:

- -Adjustable thermostatic control up to 180-190 F°
- -Insulated, solderless, stainless steel tank construction
- -Lead Free System, works with Reverse Osmosis Filtration
- -Intergrated vent works with any Waterstone Hot only or Hot & Cold faucet
- -Self re-setting thermal fuse protects from a dry start up
- -UL Listed
- -High temp push-in tank connections included
- Wall mounting bracket included
- -60 psi in-line pressure regulating valve (PRV) included
- -One year Warranty if installed with a Waterstone Faucet

Specifications:

- Capacity 5/8 gallon (2.3L). Up to 60 cups (1/2 gal) per hr
- Temperature Range Adjustable from 140F° to 190F° (60C° to 88C°)
- Heating Element 780 Watts, 6.5 amps, 120 Volts, 60 Hz
- Unit Weight 7.5 lbs
- Shipping Weight 9.0 lbs
- Tank Dimensions 11 1/4"H x 6 3/4" W x 8 1/4" D
- Water Inlet Pressure 35 psi min, to 60 psi max
- Flow Requirements Filtration must not restrict flow below 1.0 (one) GPM

